



SRST™ Z1

The Soft Ride Stand-on SRST™ Z1 is raising the bar with our patent pending adjustable operator platform, featuring suspension technology, optimizing operator comfort and increasing productivity!

The superior balance provides stability and maneuverability that exceeds expectations for traction and handling.

The Soft Ride Stand-on SRST™ Z1 is designed to allow for quick operator exit and re-entry. Need to walk away from the mower to move an obstacle or debris? The PTO will automatically disengage when the operator leaves the platform.

Restarting the blades is just as easy. When the operator steps back onto the platform and reengages the PTO switch they can continue mowing.

MODEL	ENGINE	DECK
SRSZ1KAV1936RDCE	19,0 HP* Kawasaki FX600V V-Twin Petrol	91 cm - 36" Rear discharge mower deck
SRSZ1KAV2248RDCE	22,0 HP* Kawasaki FX691V V-Twin Petrol	122 cm - 48" iCD™ Rear discharge mower deck

ENGINE GROUP

- Powered by Kawasaki V-Twin air-cooled petrol engines.
- Two-stage industrial air-cleaner.
- Easy-to-use oil drain.
- Rugged 23 litre fuel tank.

- Aluminium spindles with greaseable bearings for longer usable life.
- Factory fitted rear discharge/mulching insert and mulching blades.

OPERATOR CONTROL & COMFORT SYSTEMS

- Patent pending adjustable operator platform optimizes comfort.
- Ergonomic control panel features integrated forward and reverse levers with dual stabilizer bars.
- Ergonomic thigh pad is designed for improved comfort.
- Automatic PTO disengagement.
- Hour meter, fuel level gauge.

DRIVE TRAIN

- Dual commercial Hydro-Gear® ZT-3400® Transaxles feature 18 cm cooling fans that assist with repelling debris.
- Easy locking 3-position speed control setting.
- Large turf friendly 23" tyre for increased traction and performance.
- 13" flat-free caster tyres.

MOWER DECK

- Available in 91 cm and 122 cm cutting width with iCD™ Technology (122 cm only).
- Hand-operated height-of-cut control adjusts in 6 mm increments from 4,4 - 11,4 cm



12,8 KM/H
GROUND SPEED

UP TO **0,93**
HECTARES/HOUR

BASED ON 80% EFFICIENCY.

91 cm

UP TO **1,25**
HECTARES/HOUR

BASED ON 80% EFFICIENCY.

122 cm

* ALL POWER LEVELS ARE PROVIDED BY KAWASAKI.



The patent pending suspension platform system is adjustable for a large range of weights and operating conditions, optimizing operator comfort and increasing productivity.



Height of cut is easily changed from the operator compartment for no hassle curb climbing and trailer loading.



Generous 23 litres fuel tank is centrally located for consistent balance, and the fuel filler neck is conveniently located on the side for easy filling.



The easy locking 3-position speed control setting is conveniently located and requires no tools to facilitate smooth operation in a wide range of conditions.



Commercial Hydro-Gear® ZT-3400® Transaxles are designed for high performance and are fully serviceable.



Ergonomically designed thigh pad provides superior operator comfort, especially on uneven terrain.