

# SNAPPER® DURABILITY

<b>RPX200</b>	<b>RXT300</b>	<b>360Z - 23/42</b>	<b>360Z - 25/52</b>	<b>Model Name</b>
Rear Discharge Tractor	Rear Discharge Tractor	Zero Turn	Zero Turn	<b>Power</b>
Briggs & Stratton Intek™ Series 7220 V-Twin OHV 2 Electric Start 11 litres	Briggs & Stratton Professional Series™ 8270 V-Twin OHV 2 Electric Start 11 litres	Briggs & Stratton Professional Series™ V-Twin / 724 cc OHV, ReadyStart™ 2 Electric Start 11 litres	Briggs & Stratton Professional Series™ V-Twin / 724 cc OHV, ReadyStart™ 2 Electric Start 11 litres	Engine Model  Cylinders Starting System Fuel Capacity
Hydro-Gear® 610 0 - 9,0 km/h 0 - 4,5 km/h	Hydro-Gear® 610 0 - 9,0 km/h 0 - 4,5 km/h	Hydro-Gear® EZT® 0 - 11,0 km/h 0 - 4,0 km/h	Hydro-Gear® ZT-2800® 0 - 12,0 km/h 0 - 4,0 km/h	<b>Transmission</b> Drive Type Forward Speed Reverse Speed
Steel 15" x 6" 20" x 8" 36 cm Manual / -	Steel 15" x 6" 22" x 9,5" 36 cm Manual / -	Welded Steel 11" x 4" 20" x 8" 0 cm Mechanical - foot operated	Welded Steel 11" x 4" 20" x 10" 0 cm Mechanical - foot operated	<b>Chassis</b> Frame Tyres Front Tyres Rear Turning Radius Deck / Attachment Lift
256 cm 103 cm 120 cm 131 cm 288 kg	256 cm 112 cm 120 cm 131 cm 301 kg	183 cm 140 cm 107 cm 112 cm 238 kg	183 cm 165 cm 109 cm 112 cm 294 kg	<b>Dimensions</b> Length Width Height Wheel Base Weight
38" / 96 cm Frame Hung 350 litres Stamped Steel 7 positions / 38 - 89 mm 2	42" / 107 cm Frame Hung 350 litres Stamped Steel 7 positions / 45 - 89 mm 2	42" / 107 cm Frame Hung - Fabricated Steel 13 positions 38 - 110 mm 2	52" / 132 cm Frame Hung - Fabricated Steel 13 positions 38 - 110 mm 3	<b>Mower</b> Cutting Width Mower Deck Collector Capacity Deck Construction Height-of-Cut Range Blades