

SNAPPER® DURABILITY

SPX110	SPX210	SPX310	RPX310	Model Name
Side Discharge	Side Discharge	Side Discharge	Rear Discharge	Power
Briggs & Stratton Intek™ Series 7200 V-Twin OHV 2 Electric Start 15 litres	Briggs & Stratton Intek™ Series 7220 V-Twin OHV 2 Electric Start 15 litres	Briggs & Stratton Professional Series™ 8230 V-Twin OHV 2 Electric Start 15 litres	Briggs & Stratton Professional Series™ 8270 V-Twin OHV 2 Electric Start 11 litres	Engine Make Engine Model Cylinders Starting System Fuel Capacity
Tuff Torq® K46 0 - 7,7 km/h 0 - 5,2 km/h Rear Wheel Drive	Tuff Torq® K46 0 - 6,9 km/h 0 - 4,4 km/h Rear Wheel Drive	Tuff Torq® K46 0 - 8,2 km/h 0 - 5,4 km/h Rear Wheel Drive	Tuff Torq® K46 0 - 7,7 km/h 0 - 4,5 km/h Rear Wheel Drive	Transmission Drive Type Forward Speed Reverse Speed Configuration
Cast Iron 15" x 6" / 20" x 8" 36 cm Mechanical Electric	Cast Iron 15" x 6" / 22" x 10" 36 cm Mechanical Electric	Cast Iron 15" x 6" / 22" x 9,5" 36 cm Mechanical Electric	Cast Iron 15" x 6" / 22" x 9,5" 36 cm Mechanical Electric	Chassis Front Axle Tyres Front/Rear Turning Radius Mower Deck Lift Blade Engagement
185 x 134 x 111 cm 125 cm 211 kg	185 x 149 x 117 cm 125 cm 223 kg	185 x 150 x 117 cm 125 cm 250 kg	260 x 114 x 123 cm 125 cm 291 kg	Dimensions Assembled (LxW*xH) Wheel Base Assembled Weight
42" / 107 cm Frame Hung 4 - 7 positions / 38 - 102 mm 2 38 cm Mid-Back Yes Optional Yes	46" / 117 cm Frame Hung 4 - 7 positions / 38 - 102 mm 3 38 cm Mid-Back contoured Yes Optional Yes	48" / 122 cm Frame Hung - Fabricated 4 - 7 positions / 38 - 102 mm 3 38 cm Mid-Back contoured Yes Optional Yes	42" / 107 cm Frame Hung 4 350 litres 7 positions / 45 - 90 mm 2 38 cm Mid-Back & armrest Yes Included Yes	Mower Cutting Width Mower Deck Deck Support Wheels Collector Capacity Height-of-Cut Range Blades Seat Wash Port Mulch Kit/Plug Cruise Control