



Designed for bigger lawns, the ZTX175 and ZTX275 deliver the next level in superb all round cutting performance.

Our convertible CentreCut™ mowing technology offers total flexibility without stress of choice when buying your next zero turn mower.

The ZTX175 and ZTX275 zero turns will be delivered by your dealer with either a side or rear discharge configuration kit already fitted. Should you need a different cutting configuration in the future, then you will only need a new kit instead of buying a whole new mower deck or even a new zero turn.

With the side discharge kit fitted you will have the highest mowing capacity possible. The rear discharge kit comes with a half height mulching baffle and Eliminator® blades and provides a perfect balance between mowing capacity and mulching performance. Mounting the full height mulching baffle, which is also available as an accessory, provides you with the best mulching performance.

**CENTRECUT™**  
CONVERTIBLE MOWING TECHNOLOGY





### EASY ENGINE ACCESS

Flip up the cargo bed easily for full access to the engine compartment.



### ENGINE PROTECTION

This wrap-around steel engine enclosure helps protect critical components.



### INTUITIVE CONTROLS

Easy-to-use lawn mower controls, including an hourmeter, are all within reach.

## ZTX175

- Briggs & Stratton 7220 EXi V-Twin
- Hydro-Gear® EZT® transmissions
- 42" / 107 cm fabricated steel CentreCut™ mower deck
- Available in side or rear discharge configuration
- Forward speed: 0 - 11,0 km/h
- Reverse speed: 0 - 4,0 km/h
- Tyres front/rear: 11 x 6" / 18 x 8,5"
- **Cargo bed optional\***
- Warranty: 3-year limited

## ZTX275

- Briggs & Stratton 8240 PXi V-Twin
- Hydro-Gear® EZT® transmissions
- 48" / 122 cm fabricated steel CentreCut™ mower deck
- Available in side or rear discharge configuration
- Forward speed: 0 - 11,0 km/h
- Reverse speed: 0 - 4,0 km/h
- Tyres front/rear: 11 x 6" / 20 x 8"
- **Cargo bed included\***
- Warranty: 3-year limited
- Mid-back, premium seat

For accessories see page 30.

\* 22,7 kg. capacity, do not overload; do not carry passengers. See operator's manual for details.



See operator's manual or dealer for complete warranty details.

# ZTX

## ZERO TURN MOWERS

Model Illustrated ZTX275

# ZERO TURN MOWERS

## SPECIFICATIONS

Model Name	ZTX105	ZTX175	ZTX275	ZTX350
<b>Power</b>				
Engine Make	Briggs & Stratton	Briggs & Stratton	Briggs & Stratton	Briggs & Stratton
Engine Model	7200 EXi V-Twin OHV	7220 EXi V-Twin OHV	8240 PXi V-Twin OHV	8270 PXi V-Twin OHV
Cylinders	2	2	2	2
Starting System	Electric Start	Electric Start	Electric Start	Electric Start
Fuel Capacity	11 litres	11 litres	11 litres	11 litres
<b>Transmission</b>				
Drive Type	Hydro-Gear® EZT®	Hydro-Gear® EZT®	Hydro-Gear® EZT®	Hydro-Gear® ZT-2800®
Forward Speed	0 - 8,0 km/h	0 - 11,0 km/h	0 - 11,0 km/h	0 - 12,0 km/h
Reverse Speed	0 - 4,0 km/h	0 - 4,0 km/h	0 - 4,0 km/h	0 - 4,0 km/h
<b>Chassis</b>				
Frame	Welded Steel	Welded Steel	Welded Steel	Welded Steel
Tyres Front/Rear	11" x 4" / 18" x 6,5"	11" x 6" / 18" x 8,5"	11" x 6" / 20" x 8"	11" x 6" / 20" x 10"
Turning Radius	0 cm	0 cm	0 cm	0 cm
Mower Deck Lift	Foot operated	Foot operated	Foot operated	Foot operated
Blade Engagement	Electric	Electric	Electric	Electric
<b>Dimensions</b>				
Length	178 cm	187 cm	187 cm	187 cm
Width*	125 cm	112 cm	125 cm	167 cm
Height	107 cm	105 cm	105 cm	105 cm
Wheel Base	112 cm	112 cm	112 cm	112 cm
Weight	231 kg	237 kg	287 kg	310 kg
<b>Mower</b>				
Cutting Width	36" / 91 cm	42" / 107 cm	48" / 122 cm	52" / 132 cm
Mower Deck	Frame Hung	Frame Hung	Frame Hung	Frame Hung
Deck Construction	Fabricated Steel	Fabricated Steel	Fabricated Steel	Fabricated Steel
Deck Configuration	Side Discharge	CentreCut™	CentreCut™	Side Discharge
Deck Support Wheels	-	2	2	2
Height-of-Cut	7 positions 38 - 114 mm	13 positions 38 - 110 mm	13 positions 38 - 110 mm	13 positions 38 - 110 mm
Blades	2	2	3	3
Seat	Mid-Back & armrests	Mid-Back & armrests	Premium Mid-Back & armrests	Premium Mid-Back & armrests
Cargo bed**	Optional	Optional	Included	Included
Wash Port	Yes	Yes	Yes	Yes
Mulch Kit/Plug	Optional	Optional	Optional	Optional

\* Measured with deflector down. \*\* 22,7 kg. capacity, do not overload; do not carry passengers. See operator's manual for details.

# ZERO ZURNS

## ACCESSORIES

DESCRIPTION	PART#	ZTX105	ZTX175	ZTX275	ZTX350
		2691707	2691924	2691925	2691713
Mulch Kit for Side Discharge Deck		1697428	1697447	1697449	1696908
Mulch Kit for Rear Discharge Deck (High Rear Baffle)			84007258	84007244	
Twin Bag Collector	1697408A	•	•	•	•
Requires: Deck Boot Adapter		1697101	1697373A	1697376A	
Requires: Deck Boot Adapter + Turbo Fan					1696768A
Cargo Bed	1697133	•	•		
Cargo Bed Rhino Grips (pair)	1687855YP	•	•	•	•
Cargo Bed Rhino Grips with Ratchet (pair)	1687856YP	•	•	•	•
Light Kit	1697104	•	•	•	•
Service Jack	5601305	•	•	•	•
Requires: Service Jack Mount	5601306	•	•	•	•
Service Jack Mount		•	•	•	•
Configuration Kit Side Discharge			1697446	1697448	
Configuration Kit Rear Discharge			1697447	1697449	



### SERVICE JACK

For easy maintenance access to the underside of the mowing deck.